

Specifications of 28"

Features: 28" Carry-ON 4K broadcast director monitor.

LCD Display	LCD Size	28inch (IPS)			
	Display Resolution(Dot)	3840 × R.G.B. × 2160			
	Active area	620.93(H) ×341.28(V) mm			
	Dot pitch	0.16 (H) × 0.16(V) mm			
	Aspect Ratio	16:9			
	Brightness	450 cd/m ²			
	Contrast Ratio	1000:1			
	Light Source	LED			
	Surface treatment	3H			
	Response Time	Symbol	Min (ms)	Typical (ms)	Max (ms)
		T _R	-	1.5	2.5
		T _F	-	3.5	5.5
View Angle(Degree)	170 ° 160 °(H/V)				
Video Input Signal	HDMI, DVI, VGA,AUDIO,TALLY ,3G-SDI				
Input Connector	POWER,TALLY, VGA, DVI, HDMI, AUDIO, SDI				
Output Connector	Earphone				
Power	DC 12~24V				
Power Consumption	≤ 38W				
Control	Basic	Power, SDI,HDMI 1, HDMI2, HDMI3,HDMI4,DVI,VGA,MENU, NEXT, F1,F2,F3,F4			
	Advance	Brightness, Contrast, Saturation, Hue, harpness, emperature, acklight, Center Marker, Safety Marker, Aspect, Underscan, Check Filed, Freeze Input, Display Mode, Disp Rotate, Input, Audio, Auto adjust, H position, V position, clock, Reset, Menu Time, OSD H Position, OSD V osition.			
Speaker	Built in, 1 Watts				
Menu Language	English/Chinese				
Storage Temperature	(-20) ℃ -(+ 60)℃				
Operation Temperature	(0) ℃ -(+ 60)℃				

Operation at High Temperature and Humidity	Ta= 50℃ , 240hours
Product Dimension(mm)	670×425×45 mm
Package Contents	1. Folding sun shade cover×1 piece 2. 15V DC adapter×1 piece 3. Carry-on suitcase×1 piece 4. Battery plate bracket×1 piece 5. Manual×1 copy
Warranty	1 year parts and labor in Depot of City of Industry, CA

Note 1: Definition of response time:



