

Product Specifications

CNT-195-FR

CNT-195-FR, Cinta™ 50 Ohm Braided Coaxial Cable, black non-halogenated, fire retardant polyolefin jacket



CHARACTERISTICS

Construction Materials

Jacket Color	Black
Jacket Material	Non-halogenated, fire retardant polyolefin
Braid Material	Tinned copper
Shield Tape Material	Aluminum
Dielectric Material	Foam PE
Inner Conductor Material	Copper

Dimensions

Cable Weight	0.03 kg/m
Diameter Over Dielectric	2.790 mm 0.110 in
Diameter Over Jacket	4.950 mm 0.195 in
Inner Conductor OD	0.940 mm 0.037 in
Nominal Size	0.195 in
Outer Conductor OD	3.500 mm 0.138 in

Electrical Specifications

Cable Impedance	50 ohm
Capacitance	80 pF/m 24 pF/ft
dc Resistance, Inner Conductor	29.940 ohms/km 7.600 ohms/kft
dc Resistance, Outer Conductor	16.080 ohms/km 4.900 ohms/kft
dc Test Voltage	1500 V
Jacket Spark Test Voltage (rms)	3000 V
Maximum Frequency	37.90 GHz
Operating Frequency Band	30 – 6000 MHz
Peak Power	2.5 kW

Product Specifications

CNT-195-FR



Shielding Effectiveness	>90 dB
Velocity	75%

Environmental Specifications

Installation Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Storage Temperature	-70 °C to +85 °C (-94 °F to +185 °F)

General Specifications

Cable Type	CNT-195
Braid Coverage	89% braid
Brand	Cinta™
Packaging Type	Reel

Mechanical Specifications

Bending Moment	0.3 N-m 0.2 ft lb
Flat Plate Crush Strength	0.3 kg/mm 15.0 lb/in
Minimum Bend Radius, Single Bend	12.70 mm 0.50 in
Tensile Strength	18 kg 40 lb

Performance

Frequency	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
30 MHz	7.20	2.20
50 MHz	8.90	2.70
150 MHz	14.10	4.30
220 MHz	17.10	5.20
450 MHz	25.30	7.70
900 MHz	37.10	11.30
1500 MHz	49.50	15.10
1800 MHz	55.10	16.80
2000 MHz	58.70	17.90
2500 MHz	66.90	20.40
3000 MHz	74.80	22.80

Regulatory Compliance/Certifications

Agency
RoHS 2002/95/EC

Classification
Compliant

