

**Andrew Solutions**  
**CELLMAX-D-CPUSE****Cell-Max™ Directional In-building Antenna, 698–960 MHz, 1710–2700 MHz**

- This product is part of the CommScope Wired for Wireless® Solution

## Electrical Specifications

Frequency Band, MHz	698–800	800–960	1710–2170	2200–2700
Gain, dBi	5.0	5.0	8.0	6.0
Beamwidth, Horizontal, degrees	110	90	90	90
Beamwidth, Vertical, degrees	100.0	65.0	65.0	65.0
VSWR   Return Loss, dB	1.8:1   10.9	1.5:1   14.0	1.5:1   14.0	1.5:1   14.0
Input Power per Port, maximum, watts	50	50	50	50
Polarization	Vertical	Vertical	Vertical	Vertical
Impedance	50 ohm	50 ohm	50 ohm	50 ohm

## General Specifications

Antenna Type	Directional
Application	Indoor
Operating Frequency Band	1710 – 2700 MHz   698 – 960 MHz
Brand	Cell-Max™
Mount Type	4-hole wall mounting plate and hardware (included)
Package Quantity	1
Pigtail Cable	RG85U, plenum rated

## Mechanical Specifications

Color	White
Connector Interface	N Female
Pigtail Length	260.0 mm   10.2 in
Radome Material	ABS, UV resistant

## Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Relative Humidity	Up to 100%

## Dimensions

Height	210.00 mm   8.27 in
Length	44.00 mm   1.73 in
Width	180.00 mm   7.09 in
Net Weight	0.44 kg   0.97 lb

## Packed Dimensions

Height	55.00 mm   2.17 in
Length	250.00 mm   9.84 in
Width	190.00 mm   7.48 in

CELLMAX-D-CPUSE



Shipping Weight            0.58 kg | 1.28 lb

## Regulatory Compliance/Certifications

---

**Agency**

RoHS 2011/65/EU  
ISO 9001:2008

**Classification**

Compliant by Exemption  
Designed, manufactured and/or distributed under this quality management system

