

CONNECTIONS	
Video In	HDMI type-A x4
	HDMI type-A PGM x1
Video Out	HDMI type-A Multiview x1
	USB2.0 type-C x1(Streaming on PC)
	Assignable HDMI 1-4, PGM, Clean PGM, PWW, Color bar, Multiview
Audio In	MIC/ Line x2(3.5mm stereo audio)
PC Control Port	LAN x1
Media Library	USB type-A x1(For image import and firmware upgrade)
Tally Port	DB-15 x1
Power In	DC 12V x1
FUNCTIONS	
Transitions	T-Bar/ AUTO/ CUT
Effects	WIPE(9x2 patterns)/ MIX/ DIP/ STILL(freeze)/ PATTERN/ MUTE/ FTB
Layouts	2 styles of Multiview layout(6 windows and status)
Keys	Upstream Key: Luma Key x1/ Chroma Key x1/ PIP x2/ POP Downstream Key: DSK x1/ Logo x1
Audio Mixer	HDMI x4 and MIC/ Line x2 Audio delay: 0-500ms
Media Format	Default image: 49 preset patterns Local image: Up to 16 imported images Capture image: Up to 16 captured images
Generators	Pattern generator x1 Color generators x2
STANDARDS	
HDMI In Format Support	1080p 60/ 59.94/ 50/ 30/ 29.97/ 25/ 24/ 23.98 1080i 50/ 59.94/ 60 720p 60/ 59.94 /50/ 30/ 25/ 24 576i 50, 576p 50, 480p 59.94/ 60, 480i 59.94/ 60
HDMI PGM Out	1080p 60/ 59.94/ 50/ 48/ 47.95/ 30/ 29.97/ 25/ 24/ 23.98 1080i 60/59.94/50
HDMI Multiview Out	1080p 60/ 59.94/ 50/ 48/ 47.95/ 30/ 29.97/ 25/ 24/ 23.98 1080i 60/59.94/50
HDMI Color Space	RGB/ YUV
USB Capture Out	MJPEG, up to 1080p 60 USB disk format support: FAT32, Ext3, Ext4, up to 256GB Image format support: png, bmp, jpg, gif, jpeg, ppm, pbm, tiff, jps, mpo, tga Logo format support: png, bmp, jpg, gif, jpeg, ppm, pbm, tiff, jps, mpo, tga Logo size support: 10x10 pixel to 600x600 pixel
Media Format	
OTHERS	
Power	Wide voltage: 7-24V; Operating power:12W(12V 1A)
Dimension (LWD)	244.5 x 143.2 x 44.5mm
Weight	Net: 1030g; Gross: 1500g
Temperature	Working: -20°C-60°C, Storage: -30°C-70°C
Accessories	Power supply(12V 2A) x1; USB cable(type A-C) x1; Tally connector(DB-15) x1

